



PANLED LED panel for grid ceilings

620x620mm, matt white, 4000K

The PANLED LED PANEL comes in several light colours, which we offer in a modern, space-saving solution for an efficient type of base lighting. By means of its dimensions, the LED PANEL is particularly suitable for grid ceilings. With a luminous flux of approx. 2900 lumens, you achieve a pleasant, uniform and glare-free illumination. Electrical connections require the use of an appropriate 1000mA driver. This luminaire contains built-in LED lamps.

TECHNICAL DATA

Item no.:	1000272
Secondary power / secondary voltage	10001050 mA/V
Length	61.7 cm
Width	61.7 cm
Height	1.3 cm
Installation depth	5.0 cm
Net weight	4.245 kg
Gross weight	5.014 kg
IP Code	IP 20
Safety class	III
Assembly	Recessed
Assembly details	Ceiling
Wattage	40 W
Lumen	3650 lm
Colour temperature	4000 Kelvin
Beam angle	110 °
Color	white
CRI	>80
UGR ≤	22
Binning	6
LXXBXX data	70/50
Service life	30000 h

Accessories

158772	INSTALLATION FRAME , for LED-PANEL and I-VIDUAL, white matt, L/W/H 62.5/62.5/5.5 cm
158791	CEILING PLATE , for LED PANEL, I-VIDUAL and I-VIDUAL LED PANEL, white
158799	SUSPENSION SET , for LED PANEL, I-VIDUAL and I-VIDUAL LED PANEL, steel wire and Y-wire suspension
464032	TCI LED DRIVER , 50VA, 350-1050mA, dip switch, incl. strain relief, DALI dimmable
464170	LED DRIVER , 40W, 1000mA, incl. strain relief
464176	LED DRIVER , 40W, 1000mA, incl. strain relief, dimmable
464804	LED DRIVER , 40W, 1050mA, triac dimmable

Notes
