



PANLED LED panel for grid ceilings

595x595mm, matt white, 3000K

The 60x60 cm grid PANLED LED PANEL, available with a number of different colours of light, offers a modern and space saving solution for efficient basic lighting needs. Due to the variable constant current power supply of 1000mA to 1050mA, various standard or dimmable drivers can be used. With this product you reach a pleasant, homogenous and glare-free lighting feeling.

TECHNICAL DATA

Item no.:	1000269
Secondary power / secondary voltage	10001050 mA/V
Length	59.5 cm
Width	59.5 cm
Height	1.3 cm
Installation depth	5.0 cm
Net weight	3.923 kg
Gross weight	4.643 kg
IP Code	IP 20
Safety class	III
Assembly	Recessed
Assembly details	Ceiling
Wattage	40 W
Lumen	3250 lm
Colour temperature	3000 Kelvin
Beam angle	110 °
Color	white
CRI	>80
UGR ≤	22
Binning	6
LXXBXX data	70/50
Service life	30000 h

Accessories

158762	INSTALLATION FRAME , for LED-PANEL, I-VIDUAL and I-VIDUAL PANEL, matt white, L/W/H 60/60/5.5 cm
158791	CEILING PLATE , for LED PANEL, I-VIDUAL and I-VIDUAL LED PANEL, white
158799	SUSPENSION SET , for LED PANEL, I-VIDUAL and I-VIDUAL LED PANEL, steel wire and Y-wire suspension
464032	TCI LED DRIVER , 50VA, 350-1050mA, dip switch, incl. strain relief, DALI dimmable
464170	LED DRIVER , 40W, 1000mA, incl. strain relief
464176	LED DRIVER , 40W, 1000mA, incl. strain relief, dimmable
464804	LED DRIVER , 40W, 1050mA, triac dimmable

Notes
