


## **CADRA** recessed fitting

## square, silver-grey, warm-white LED

With our CADRA series we offer you a lighting solution for recessed wall and ceiling installation with minimum space requirements. The LED version is equipped with a durable diode and available in either blue, neutral or warm white light colour. A suitable constant current driver rated at 350mA is needed to operate the CADRA. The optional accessory includes a connector strip for simplified wiring in addition to the mounting box and flush-mount frame. This luminaire contains built-in LED lamps.



## **TECHNICAL DATA**

Item no.:	1000241
Lamps included	0
Secondary power / secondary voltage	350 mA/V
Width	9.0 cm
Height	9.0 cm
Depth	4.0 cm
Installation length	8.1 cm
Installation width	6.9 cm
Installation depth	4.5 cm
Net weight	0.155 kg
Gross weight	0.208 kg
IP Code	IP 20
Safety class	III
Assembly	Recessed
Assembly details	Wall
Wattage	1 W
Lumen	90 lm
Colour temperature	3000 Kelvin
Color	grey
CRI	>80
LXXBXX data	70/50
Service life	30000 h
	•

						-				4			-		-		-	4	-	4	-	-	-	-	4	-									
	4	4	- 4	4	4	J	J	J	a,	J	J	J	J	J	4	4	J	a,																	
ı J	JJ	١.,	1	J	J	J	J	J	ä	J	J	J	J	J	J	J		a.			4		1		4	J	1	ı	ı	a,	ı	ı	J,	1	١,
				- 6					- 6		- 1	- 1	- 1	- 1												-									



## Accessories

111850	MULTIWAY CONNECTOR , 3 outputs with two bridges, black, max. 350mA
112780	FLUSH-MOUNTED FRAME , for FRAME BASIC, FLAT FRAME BASIC, FLAT FRAME CURVE and FRAME CURVE
112781	MOUNTING BOX for FRAME BASIC , FLAT FRAME BASIC, FLAT FRAME CURVE and FRAME CURVE
464107	LED DRIVER , 3VA, 350mA, with AMP plug, incl. strain relief

Notes		