





P-LIGHT

recessed fitting, LED, 6000K, round, white, 5W

P-LIGHT suitable for use as emergency lighting for wall and ceiling installation. The two rigid lamp heads are each fitted with a 2W LED. The safety lights are fitted with two built-in Ni-MH rechargeable batteries and an auto test function. The emergency operating time of the luminaires is three hours. The luminaires can be operated permanently switched on / stand-by operation. The electrical connection is directly to the 230V supply. Other variants of the P-LIGHT series are available.



TECHNICAL DATA

Item no.:	240006
Lamps included	0
Number of different light outlets	1
Primary nominal voltage	220-240V ~50Hz mA/V
Height	6.2 cm
Diameter	12.5 cm
Installation diameter	9.5 cm
Installation depth	7.5 cm
Net weight	0.408 kg
Gross weight	0.491 kg
IP Code	IP 20
Safety class	II
Assembly	Recessed
Assembly details	Ceiling
Wattage	5 W
Lumen	120 lm
Colour temperature	6000 Kelvin
Beam angle	90 °
Color	white
CRI	>70
LXXBXX data	70/50
Service life	25000 h



BIG WHITE Page	405
----------------	-----

Accessories

240024	RECHARGEABLE BATTERY , for P-LIGHT, 7.2V, 1000mA
--------	--

Notes
