





F-LIGHT recessed fitting

LED, 3000K, round, white, 60°, rigid, 6.35W

The F-LIGHT is fitted with an integrated 6.35W LED. The recessed light is made of aluminium, steel and plastic and is fitted with a warm-white LED. Next to the white housing colour, an additional cover is available in white, black or chrome. The fire-resistant recessed fitting for standard-compliant increased fire protection in F90 ceilings. A suitable constant current driver providing 350mA is required to operate the recessed fitting. This luminaire contains built-in LED lamps and is available in various beam angles. Optionally, a funnel-shaped or flat decorative frame can be used.



TECHNICAL DATA

Item no.:	114061
Lamps included	0
Secondary power / secondary voltage	350 mA/V
Height	5.0 cm
Diameter	8.0 cm
Net weight	0.197 kg
Gross weight	0.23 kg
IP Code	IP 20
Safety class	III
Assembly	Recessed
Assembly details	Ceiling with Acc.
Wattage	8.8 W
Lumen	690 lm
Colour temperature	3000 Kelvin
Beam angle	60 °
Color	white
CRI	>80
Binning	6

Accessories

114070	COVER for F-LIGHT recessed fitting , funnel-shaped, black, with clear glass
114071	COVER for F-LIGHT recessed fitting , funnel-shaped, white, with clear glass
114080	COVER for F-LIGHT recessed fitting , round, flat, black, with clear glass
114081	COVER for F-LIGHT recessed fitting , round, flat, white, with clear glass
114082	COVER for F-LIGHT recessed fitting , round, flat, chrome, with clear glass

Notes
