




## DOLIX OUT

Outdoor recessed fitting, QR-C51, IP65, round, silver-grey, max. 35W, incl. clip springs

The DOLIX low-voltage recessed ceiling ring is made from aluminium and is equipped with a glass for protection against splashing water. Rated IP65 it can be used outdoors or in damp areas. To operate the recessed fitting, a matching transformer for low-voltage halogen lamps is required.



## TECHNICAL DATA

Item no.:	111008
Socket	GX5.3
Lamp	QR-C51
Number of sockets	1
Lamps included	0
Primary nominal voltage	12V ~50Hz mA/V
Width	14.0 cm
Depth	8.0 cm
Installation diameter	7.0 cm
Installation depth	13.5 cm
Net weight	0.308 kg
Gross weight	0.343 kg
IP Code	IP 65
Safety class	III
Assembly	Recessed
Assembly details	Ceiling
Wattage	35 W
Color	grey

## Recommended lamp

1001574	Philips Master LED Spot MR16 , 5W, 2700K, 36°, dimmable
1001575	Philips Master LED MR16 5W , 3000K, 36°
551862	LED QR-C51 , lamp, 5W, COB LED, 38°, 2700K, not dimmable

## Accessories

227160	TRANSFORMER , 60VA, 12V, IP44
--------	-------------------------------

## Notes

---

---

---

---

---