

DOWNUNDER 14

outdoor wall light, LED, 3000K, IP44, brushed aluminium, 0.8W

Aluminium recessed wall light of the DOWNUNDER series. The built-in concealed SMD LEDs emit their light indirectly to the surface to be illuminated. As a result, for example, glare-free illumination of walkways is enabled. The electrical connection is made directly to the 230V mains supply. Thanks to its IP44 protection class, the luminaire is suitable for outdoor use. The DOWNUNDER series also includes versions with other shapes as well as housing and light colours.

TECHNICAL DATA

Item no.:	230302
Lamps included	0
Primary nominal voltage	230V ~50Hz mA/V
Diameter	12.5 cm
Depth	6.0 cm
Installation diameter	11.5 cm
Installation depth	7.2 cm
Net weight	0.361 kg
Gross weight	0.426 kg
IP Code	IP 44
Safety class	II
Assembly	Recessed
Assembly details	Wall
Number of through-wires	10
Wattage	0.8 W
Lumen	32 lm
Colour temperature	3000 Kelvin
Color	aluminium
CRI	>80
LXXBXX data	70/50
Service life	20000 h
	•

							ч				4			ч		4		ч	ч	ч	ч	4	7	ч	ч	ч	4									
	- 4	- 4		a,	a,	J.	J.	J	J	J	J	J	J	J	ä	ä	ä	ä	J.																	
ı	LL	1 1	ı	J	J	J	J	J.	J	ä	J	J	J	J	J	J	J		4			ı		4		1	4	1	ı	ı	a,	J.	ı	ı	1	١,
					á			á		ä		J	ä	J	ä	J	J	J	J.	J	J.	a.	J.	J	J	J	J.	ă,								



Notes				