



DOWNUNDER RCL 101

recessed fitting, LED, 3000K, square, brushed stainless steel, 2W, incl. clip springs

Aluminium recessed wall light of our DOWNUNDER RCL 101 series. The not visibly mounted SMD LED lamp emits the light indirectly onto the surface to be illuminated in neutral or warm white colour. This guarantees glare-free illumination of walkways and much more. To operate the DOWNUNDER RCL 101, a suitable LED power supply is required providing 24V direct current. A mounting frame for installation in masonry can be ordered from the accessory. This luminaire contains built-in LED lamps.

TECHNICAL DATA

Item no.:	152062
Lamps included	0
Primary nominal voltage	24V mA/V
Width	12.5 cm
Height	6.5 cm
Depth	4.7 cm
Installation width	11.4 cm
Net weight	0.258 kg
Gross weight	0.334 kg
IP Code	IP 20
Safety class	III
Assembly	Recessed
Assembly details	Wall
Wattage	2.4 W
Lumen	90 lm
Colour temperature	3000 Kelvin
Color	stainless steel
CRI	>80
Binning	6
LXXBXX data	70/50
Service life	20000 h



Accessories

470502	LED POWER SUPPLY , 12W, 24V
925201	FLUSH-MOUNTED FRAME , for DOWNUNDER RCL 101, galvanised steel

Notes
