





ANINDA

wall and recessed ceiling light, LED, 3000K, short, white, 90°

The rectangular ANINDA is a professional recessed ceiling and wall light which has been specially manufactured for hollow ceilings and walls. The light outlet is covered by acrylic glass. A suitable constant current driver providing 700mA is required to operate the recessed luminaire.



TECHNICAL DATA

| | |
|-------------------------------------|---------------|
| Item no.: | 1000387 |
| Lamps included | 0 |
| Secondary power / secondary voltage | 700 mA/V |
| Length | 60.5 cm |
| Width | 5.8 cm |
| Height | 8.6 cm |
| Installation length | 59.0 cm |
| Installation width | 4.5 cm |
| Installation depth | 8.5 cm |
| Net weight | 1.069 kg |
| Gross weight | 1.43 kg |
| IP Code | IP 20 |
| Safety class | III |
| Assembly | Recessed |
| Assembly details | Ceiling, Wall |
| Wattage | 16 W |
| Lumen | 1040 lm |
| Colour temperature | 3000 Kelvin |
| Beam angle | 90 ° |
| Color | white |
| CRI | >80 |
| Binning | 3 |

Accessories

| | |
|---------|---|
| 1001133 | LED driver , 700mA, 12.5-25W, dimmable |
| 1001136 | LED driver , 700mA, 12.6-19.6W |
| 464032 | TCI LED DRIVER , 50VA, 350-1050mA, dip switch, incl. strain relief, DALI dimmable |

Notes
