





## ANINDA

wall and recessed ceiling light, LED, 3000K, long, white, 90°

The rectangular ANINDA is a professional recessed ceiling and wall light which has been specially manufactured for hollow ceilings and walls. The light outlet is covered by acrylic glass. A suitable constant current driver providing 700mA is required to operate the recessed luminaire.



## TECHNICAL DATA

Item no.:	1000390
Lamps included	0
Secondary power / secondary voltage	700 mA/V
Length	120.5 cm
Width	5.8 cm
Height	8.6 cm
Installation length	119.0 cm
Installation width	4.5 cm
Installation depth	8.5 cm
Net weight	1.995 kg
Gross weight	2.547 kg
IP Code	IP 20
Safety class	III
Assembly	Recessed
Assembly details	Ceiling, Wall
Wattage	31 W
Lumen	2230 lm
Colour temperature	3000 Kelvin
Beam angle	90 °
Color	white
CRI	>80
Binning	3

## Accessories

1001114	LED driver , 700mA, 40W, dimmable
1001132	LED driver , 700mA, 19-35W, dimmable
464032	TCI LED DRIVER , 50VA, 350-1050mA, dip switch, incl. strain relief, DALI dimmable
464168	LED DRIVER , 40W, 700mA, incl. strain relief

## Notes

---

---

---

---

---