





## **ALAMEA**

recessed ceiling light, LED, 3000K, white, 36W

The ALAMEA recessed ceiling light for commercial applications and applications needing clear light properties. Available with a black or white housing, the ALAMEA is equipped with a powerful 35 Watt LED. The LED insert, which is available in two light colours, is telescopic and adjustable, and can therefore be flexibly directed. A suitable LED constant current driver is required to operate the recessed fitting. This luminaire has a built-in LED module.





## **TECHNICAL DATA**

Item no.:	1000792
Secondary power / secondary voltage	1000 mA/V
Vertical tilting range	60 °
Length	24.6 cm
Width	15.6 cm
Height	11.3 cm
Installation length	22.5 cm
Installation width	13.0 cm
Installation depth	11.3 cm
Net weight	2.232 kg
Gross weight	2.485 kg
IP Code	IP 20
IP Code Safety class	IP 20
Safety class	
Safety class Assembly	III Recessed
Safety class Assembly Assembly details	III Recessed Ceiling
Safety class Assembly Assembly details Wattage	III Recessed Ceiling 36 W
Safety class Assembly Assembly details Wattage Lumen	III Recessed Ceiling 36 W 3600 Im
Safety class Assembly Assembly details Wattage Lumen Colour temperature	III Recessed Ceiling 36 W 3600 Im 3000 Kelvin
Safety class Assembly Assembly details Wattage Lumen Colour temperature Color	III Recessed Ceiling 36 W 3600 Im 3000 Kelvin white
Safety class Assembly Assembly details Wattage Lumen Colour temperature Color	III Recessed Ceiling 36 W 3600 Im 3000 Kelvin white >90





## Accessories

1001115	LED driver , 1000mA, 40W, dimmable
464032	TCI LED DRIVER , 50VA, 350-1050mA, dip switch, incl. strain relief, DALI dimmable
464170	LED DRIVER , 40W, 1000mA, incl. strain relief

Service life	35000 h
BIG WHITE Page	452

Notes		