



## **MEDO 30**

recessed fitting, LED, 3000K, frameless, white, 1-10V

The high-quality MEDO 30 recessed ceiling light convinces with its clear form and the simple integration provided by its frameless installation. The MEDO 30 is dimmable via a 1-10V interface. Its integrated Premium LED gives pleasant lighting effects, and its built-in LED driver allows direct connection to 230V mains supply.





## **TECHNICAL DATA**

| Item no.:                           | 1000850                |  |  |
|-------------------------------------|------------------------|--|--|
| Primary nominal voltage             | 220-240V ~50/60Hz mA/V |  |  |
| Secondary power / secondary voltage | 350 mA/V               |  |  |
| Height                              | 11.0 cm                |  |  |
| Diameter                            | 28.0 cm                |  |  |
| Installation diameter               | 29.0 cm                |  |  |
| Installation depth                  | 15.0 cm                |  |  |
| Net weight                          | 1.094 kg               |  |  |
| Gross weight                        | 1.585 kg               |  |  |
| IP Code                             | IP 20                  |  |  |
| Safety class                        | I                      |  |  |
| Assembly                            | Recessed               |  |  |
| Assembly details                    | Ceiling                |  |  |
| Dimming technology                  | 1-10V                  |  |  |
| Wattage                             | 15 W                   |  |  |
| Lumen                               | 1000 lm                |  |  |
| Colour temperature                  | 3000 Kelvin            |  |  |
| Beam angle                          | 105 °                  |  |  |
| Color                               | white                  |  |  |
| CRI                                 | >80                    |  |  |
| UGR≤                                | 25                     |  |  |
| Binning                             | 6                      |  |  |





| LXXBXX data  | 70/50   |
|--------------|---------|
| Service life | 25000 h |

| Notes |  |  |  |
|-------|--|--|--|
|       |  |  |  |
|       |  |  |  |
|       |  |  |  |
|       |  |  |  |
|       |  |  |  |
|       |  |  |  |
|       |  |  |  |
|       |  |  |  |
|       |  |  |  |