а – ы ы з – ы ы н ы Ъ ы ы J.






LIGHTPOINT

recessed fitting, LED, round, matt white, 3000K

The LIGHTPOINT LED point outlet is available in housing colours white and brushed aluminium. A suitable LED driver operates the recessed light.



TECHNICAL DATA

| Item no.: | 1001156 |
|-------------------------------------|-------------|
| Lamps included | 0 |
| Secondary power / secondary voltage | 350 mA/V |
| Height | 4.6 cm |
| Diameter | 3.75 cm |
| Installation diameter | 3.4 cm |
| Installation depth | 3.0 cm |
| Net weight | 0.058 kg |
| Gross weight | 0.079 kg |
| IP Code | IP 20 |
| Safety class | 111 |
| Assembly | Recessed |
| Assembly details | Ceiling |
| Wattage | 1 W |
| Lumen | 100 lm |
| Colour temperature | 3000 Kelvin |
| Color | white |
| CRI | >80 |
| Binning | 6 |
| LXXBXX data | 70/50 |
| Service life | 30000 h |
| BIG WHITE Page | 392 |
| | |

Accessories

| 111850 | MULTIWAY CONNECTOR , 3 outputs with two bridges, black, max. 350mA |
|--------|--|
| 464107 | LED DRIVER , 3VA, 350mA, with AMP plug, incl. strain relief |

Notes