



## DOLIX OUT QR-C51

square, chrome

The DOLIX OUT low-voltage recessed ceiling light is made from aluminium and is equipped with a glass for protection against splashing water. Rated IP65 it can be used outdoors or in damp areas. To operate the recessed fitting, a matching transformer for low-voltage halogen lamps is required.

### TECHNICAL DATA

|                         |                            |
|-------------------------|----------------------------|
| Item no.:               | 1001162                    |
| Socket                  | GX5.3                      |
| Lamp                    | QR-C51                     |
| Number of sockets       | 1                          |
| Lamps included          | 0                          |
| Primary nominal voltage | 12V ~50Hz mA/V             |
| Length                  | 8.8 cm                     |
| Width                   | 8.8 cm                     |
| Height                  | 11.0 cm                    |
| Installation diameter   | 6.8 cm                     |
| Installation depth      | 11.0 cm                    |
| Net weight              | 0.184 kg                   |
| Gross weight            | 0.212 kg                   |
| IP Code                 | IP 65                      |
| Safety class            | III                        |
| Impact resistance class | IK02                       |
| Impact resistance       | 0,200000000000000001 Joule |
| Assembly                | Recessed                   |
| Assembly details        | Ceiling                    |
| Wattage                 | 50 W                       |
| Color                   | chrome                     |

## Recommended lamp

|         |  |
|---------|--|
| 1001574 | Philips Master LED Spot MR16 , 5W, 2700K, 36°, dimmable  |
| 1001575 | Philips Master LED MR16 5W , 3000K, 36°                  |
| 551862  | LED QR-C51 , lamp, 5W, COB LED, 38°, 2700K, not dimmable |

## Notes

---

---

---

---

---