




DOLIX OUT QPAR51

round, chrome

The DOLIX OUT high-voltage recessed ceiling ring is made from aluminium and is equipped with a glass for protection against splashing water. Rated IP65 it can be used outdoors or in damp areas. Thanks to the already incorporated GU10 high-voltage socket, the DOLIX OUT recessed ceiling ring is ready for direct connection to 230V mains supply.



TECHNICAL DATA

| | |
|-------------------------|----------------------------|
| Item no.: | 1001166 |
| Socket | GU10 |
| Lamp | QPAR51 |
| Number of sockets | 1 |
| Lamps included | 0 |
| Primary nominal voltage | 220-240V ~50/60Hz mA/V |
| Height | 11.0 cm |
| Diameter | 8.2 cm |
| Installation diameter | 6.8 cm |
| Installation depth | 11.0 cm |
| Net weight | 0.192 kg |
| Gross weight | 0.234 kg |
| IP Code | IP 65 |
| Safety class | II |
| Impact resistance class | IK02 |
| Impact resistance | 0,200000000000000001 Joule |
| Assembly | Recessed |
| Assembly details | Ceiling |
| Wattage | 50 W |
| Color | chrome |
| BIG WHITE Page | 402 |

Recommended lamp

| | |
|---------|--|
| 1001030 | LED QPAR51 GU10 , lamp, 38°, 2700K, 400 lm, dimmable |
| 1004972 | LED QPAR51 , lightbulb GU10 2700K° |
| 1005075 | LED lightbulb QPAR51 , GU10, 2700K, grey |
| 1005078 | LED lightbulb QPAR51 , GU10, 3000K, grey |

Notes
