




I-VIDUAL PANEL 600x600

LED Indoor recessed ceiling light, UGR<19 4000K

The I-VIDUAL, which is available in several light colours, is a modern and space saving solution for an efficient type of basic lighting. With this product you reach a pleasant, homogeneous and glare-free lighting feeling. An aperture angle under 19° is achieved here.



TECHNICAL DATA

Item no.:	1001444
Lamps included	0
Secondary power / secondary voltage	10001050 mA/V
Length	59.5 cm
Width	59.5 cm
Height	1.3 cm
Installation depth	5.0 cm
Net weight	3.7 kg
Gross weight	3.959 kg
IP Code	IP 20
Safety class	III
Assembly	Recessed
Assembly details	Ceiling,Ceiling with Acc.
Wattage	35 W
Lumen	3700 lm
Colour temperature	4000 Kelvin
Beam angle	90 °
Color	white
CRI	>80
UGR ≤	19
Binning	6
LXXBXX data	70/50

Service life

30000 h

Accessories

158762	INSTALLATION FRAME , for LED-PANEL, I-VIDUAL and I-VIDUAL PANEL, matt white, L/W/H 60/60/5.5 cm
158764	INSTALLATION FRAME , for I-VIDUAL LED panel, silver-grey, L/W 60.5/60.5 cm
158791	CEILING PLATE , for LED PANEL, I-VIDUAL and I-VIDUAL LED PANEL, white
158799	SUSPENSION SET , for LED PANEL, I-VIDUAL and I-VIDUAL LED PANEL, steel wire and Y-wire suspension
464032	TCI LED DRIVER , 50VA, 350-1050mA, dip switch, incl. strain relief, DALI dimmable
464170	LED DRIVER , 40W, 1000mA, incl. strain relief
464176	LED DRIVER , 40W, 1000mA, incl. strain relief, dimmable
464804	LED DRIVER , 40W, 1050mA, triac dimmable

Notes
