




I-VIDUAL PANEL 620x620

LED Indoor recessed ceiling light, UGR<19 3000K

The I-VIDUAL, which is available in several light colours, is a modern and space saving solution for an efficient type of basic lighting. With this product you reach a pleasant, homogeneous and glare-free lighting feeling. An aperture angle under 19° is achieved here.



TECHNICAL DATA

Item no.:	1001445
Lamps included	0
Secondary power / secondary voltage	10001050 mA/V
Length	61.7 cm
Width	61.7 cm
Height	1.3 cm
Installation depth	5.0 cm
Net weight	4.0 kg
Gross weight	4.28 kg
IP Code	IP 20
Safety class	III
Assembly	Recessed
Assembly details	Ceiling,Ceiling with Acc.
Wattage	35 W
Lumen	3700 lm
Colour temperature	3000 Kelvin
Beam angle	90 °
Color	white
CRI	>80
UGR ≤	19
Binning	6
LXXBXX data	70/50

Service life

30000 h

Accessories

158772	INSTALLATION FRAME , for LED-PANEL and I-VIDUAL, white matt, L/W/H 62.5/62.5/5.5 cm
158774	INSTALLATION FRAME , for I-VIDUAL LED panel, silver-grey, L/W 62.5/62.5 cm
158791	CEILING PLATE , for LED PANEL, I-VIDUAL and I-VIDUAL LED PANEL, white
158799	SUSPENSION SET , for LED PANEL, I-VIDUAL and I-VIDUAL LED PANEL, steel wire and Y-wire suspension
464032	TCI LED DRIVER , 50VA, 350-1050mA, dip switch, incl. strain relief, DALI dimmable
464170	LED DRIVER , 40W, 1000mA, incl. strain relief
464176	LED DRIVER , 40W, 1000mA, incl. strain relief, dimmable
464804	LED DRIVER , 40W, 1050mA, triac dimmable

Notes
