


RILO DL

LED indoor recessed ceiling light, white/chrome, 3000/4000K, 5.5W

RILO series LED recessed ceiling lights impress with their innovative technology. The light colour can be adjusted via a switch during installation, and the UGR value is less than 19 and the Cri is greater than 90! The luminaire, which is available with a white housing, is connected directly to the 230V mains voltage supply.



TECHNICAL DATA

Item no.:	1001973	
Primary nominal voltage	220-240V ~50/60Hz mA/V	
Secondary power / secondary voltage	75 mA/V	
Height	7.0 cm	
Diameter	11.0 cm	
Installation diameter	9.0 cm	
Installation depth	8.0 cm	
Net weight	0.175 kg	
Gross weight	0.276 kg	
IP Code	IP 20	
Safety class	I	
Assembly	Recessed	
Assembly details	Ceiling	
Wattage	6 W	
Lumen	350 / 400 lm	
	0007 400 1111	
Colour temperature	3000/4000 Kelvin	
Colour temperature Beam angle		
	3000/4000 Kelvin	
Beam angle	3000/4000 Kelvin 60 °	
Beam angle Color	3000/4000 Kelvin 60 ° white	
Beam angle Color CRI	3000/4000 Kelvin 60 ° white >90	
Beam angle Color CRI UGR ≤	3000/4000 Kelvin 60 ° white >90 19	





Service life	25000 h
--------------	---------

Notes		