


DL 126

recessed fitting, LED SMD, 3000K, round, white, max. 3W, incl. leaf springs

The DL 126 recessed fitting impresses with its low height and it is therefore ideal for use with low installation depths. The six long-life SMD LEDs with a total power output of 3W ensure that you have the necessary level of illumination. The recessed fitting is available with a shutter coloured white, chrome and brushed metal. A suitable 12V direct current power supply is needed for operation. This luminaire contains built-in warm-white LED lamps.



TECHNICAL DATA

| | |
|-------------------------|---------------|
| Item no.: | 112221 |
| Lamps included | 0 |
| Primary nominal voltage | 12V mA/V |
| Height | 1.6 cm |
| Diameter | 6.5 cm |
| Installation diameter | 5.7 cm |
| Installation depth | 1.4 cm |
| Net weight | 0.121 kg |
| Gross weight | 0.144 kg |
| IP Code | IP 20 |
| Safety class | III |
| Assembly | Recessed |
| Assembly details | Ceiling, Wall |
| Wattage | 2.8 W |
| Lumen | 160 lm |
| Colour temperature | 3000 Kelvin |
| Beam angle | 90 ° |
| Color | white |
| CRI | >80 |
| Binning | 6 |
| LXXBXX data | 70/50 |
| Service life | 30000 h |

Accessories

| | |
|--------|---|
| 112175 | INSTALLATION FRAME , for DL 126 recessed fitting, triangle, brushed metal |
| 112181 | INSTALLATION FRAME , for DL 126 recessed fitting, round, white |
| 112182 | INSTALLATION FRAME , for DL 126 recessed fitting, round, chrome |
| 112185 | INSTALLATION FRAME , for DL 126 recessed fitting, round, brushed metal |
| 470507 | LED POWER SUPPLY , 12W, 12V |

Notes
