


DEKLED

recessed fitting, LED, 4000K, round, silver metallic, 1W

The rigid LED recessed spot, DEKLED is made of aluminium and is the LED light solution for applications where point accent lighting and low installation depth is needed. The optionally available in pure or warm white 1W LED provides the needed light intensity. To operate, the spot needs a suitable constant current driver rated at 350mA. This luminaire contains built-in LED lamps.



TECHNICAL DATA

| Item no.: | 112240 |
|-------------------------------------|---------------|
| Lamps included | 0 |
| Secondary power / secondary voltage | 350 mA/V |
| Height | 2.0 cm |
| Diameter | 3.0 cm |
| Installation diameter | 2.5 cm |
| Installation depth | 1.5 cm |
| Net weight | 0.045 kg |
| Gross weight | 0.067 kg |
| IP Code | IP 20 |
| Safety class | III |
| Assembly | Recessed |
| Assembly details | Ceiling, Wall |
| Wattage | 1 W |
| Lumen | 60 lm |
| Colour temperature | 4000 Kelvin |
| Beam angle | 45 ° |
| Color | grey |
| CRI | >80 |
| LXXBXX data | 70/50 |
| Service life | 30000 h |
| BIG WHITE Page | 000 |
| BIG WHITE Fage | 393 |

| | | | | | | | 4 | | | | 4 | | | 4 | | 4 | | -4 | 4 | 4 | 4 | ч | 4 | 4 | 4 | 4 | 4 | | | | | | | | | |
|----|----|-----|---|---|----|----|----|----|----|----|---|---|---|---|----|----|----|----|---|---|---|---|----|---|---|---|----|---|---|---|---|---|---|---|---|----|
| | a, | _1 | | ä | a, | J. | J. | J. | a, | a, | J | J | J | J | ä | ä | ä | ä | ä | | | | | | | | | | | | | | | | | |
| ı, | J | ר ר | J | J | J | J | J | J | a, | a. | J | J | a | J | J | J | J | | 4 | | | J | | ı | | 1 | J. | 1 | ı | ı | 1 | ı | ı | L | 1 | ١, |
| | | | | | п | | | п | | 1 | | 1 | 1 | п | Э. | Э. | Э. | | п | 1 | 1 | п | а. | 1 | 1 | п | п | т | | | | | | | | |



Accessories

| 464108 | LED DRIVER , 3W, 320mA, incl. strain relief |
|--------|---|
| | |

| Notes | | |
|-------|--|--|
| | | |
| | | |
| | | |
| | | |
| | | |