


FLAT FRAME

recessed fitting, QT9, square, silver-grey, max. 20W, incl. leaf springs

With our FLAT FRAME series we offer you a lighting solution for recessed wall and ceiling installation with minimum space requirements. Ready for the use of G4 pin-based lamps, a suitable transformer providing 12V alternating current is required for operation. An installation frame and a wall box are both available on accessory.



TECHNICAL DATA

Item no.:	112772
Socket	G4
Lamp	QT9
Number of sockets	1
Lamps included	0
Primary nominal voltage	12V ~50/60Hz mA/V
Width	9.0 cm
Height	9.0 cm
Depth	4.8 cm
Installation length	7.5 cm
Installation width	7.5 cm
Installation depth	4.5 cm
Net weight	0.149 kg
Gross weight	0.207 kg
IP Code	IP 20
Safety class	III
Assembly	Recessed
Assembly details	Ceiling, Wall
Wattage	20 W
Color	grey
BIG WHITE Page	385
	-

							4				4			4		4		-	4	-	4	ч.	4	ч,	4	4	4									
	- 4	- 4		a,	a,	J	J	J	J	a	J	J	J	J	ä	a,	ä	ā,	ä																	
ı	1 1	1 1	1	J	J	J	J	J	ä	4	ā	J	J	J	J	J	4		4			1		1		1	1	1	J,	4	a,	1	ı	. د	, د	ı
					п			п		м		п	4	4	1	1	п		1		4	1	1	1		1	п	4								



Accessories

112780	FLUSH-MOUNTED FRAME , for FRAME BASIC, FLAT FRAME BASIC, FLAT FRAME CURVE and FRAME CURVE						
112781	MOUNTING BOX for FRAME BASIC , FLAT FRAME BASIC, FLAT FRAME CURVE and FRAME CURVE						
461060	MINI TRANSFORMER 1 , 60VA, 12V, L/- W/H 10.5/3.3/2.2 cm						

Notes			