





FRAME CURVE

recessed fitting, LED, 4000K, square, matt white, incl. leaf springs

With our FRAME series we offer you a lighting solution for recessed wall and ceiling installation with minimum space requirements. The LED version is equipped with a durable diode and available in either pure white or warm white light colour. To operate, the FRAME CURVE needs a suitable constant current driver rated at 350mA. The optional accessory includes a connector strip for simplified wiring in addition to the mounting box and flush-mount frame. This luminaire contains built-in LED lamps.



TECHNICAL DATA

Item no.:	113290
Lamps included	0
Secondary power / secondary voltage	350 mA/V
Width	9.0 cm
Height	9.0 cm
Depth	4.0 cm
Installation length	8.1 cm
Installation width	6.9 cm
Installation depth	4.5 cm
Net weight	0.158 kg
Gross weight	0.213 kg
IP Code	IP 20
Safety class	III
Assembly	Recessed
Assembly details	Wall
Lumen	60 lm
Colour temperature	4000 Kelvin
Color	white
CRI	>80
LXXBXX data	70/50
Service life	30000 h
BIG WHITE Page	385

Accessories

111850	MULTIWAY CONNECTOR , 3 outputs with two bridges, black, max. 350mA
111861	CABLE EXTENSION , for items with a 350mA plug, 1 m
112780	FLUSH-MOUNTED FRAME , for FRAME BASIC, FLAT FRAME BASIC, FLAT FRAME CURVE and FRAME CURVE
112781	MOUNTING BOX for FRAME BASIC , FLAT FRAME BASIC, FLAT FRAME CURVE and FRAME CURVE
464107	LED DRIVER , 3VA, 350mA, with AMP plug, incl. strain relief

Notes
