





FRAME CURVE

recessed fitting, LED, 3000K, square, matt white, incl. leaf springs

With our FRAME series we offer you a lighting solution for recessed wall and ceiling installation with minimum space requirements. The LED version is equipped with a durable diode and available in either pure white or warm white light colour. To operate, the FRAME CURVE needs a suitable constant current driver rated at 350mA. The optional accessory includes a connector strip for simplified wiring in addition to the mounting box and flush-mount frame. This luminaire contains built-in LED lamps.



TECHNICAL DATA

| | |
|-------------------------------------|-------------|
| Item no.: | 113292 |
| Lamps included | 0 |
| Secondary power / secondary voltage | 350 mA/V |
| Width | 9.0 cm |
| Height | 9.0 cm |
| Depth | 4.0 cm |
| Installation length | 8.1 cm |
| Installation width | 6.9 cm |
| Installation depth | 4.5 cm |
| Net weight | 0.159 kg |
| Gross weight | 0.219 kg |
| IP Code | IP 20 |
| Safety class | III |
| Assembly | Recessed |
| Assembly details | Wall |
| Wattage | 1 W |
| Lumen | 60 lm |
| Colour temperature | 3000 Kelvin |
| Color | white |
| CRI | >90 |
| LXXBXX data | 70/50 |
| Service life | 30000 h |

Accessories

| | |
|--------|---|
| 111850 | MULTIWAY CONNECTOR , 3 outputs with two bridges, black, max. 350mA |
| 111861 | CABLE EXTENSION , for items with a 350mA plug, 1 m |
| 112780 | FLUSH-MOUNTED FRAME , for FRAME BASIC, FLAT FRAME BASIC, FLAT FRAME CURVE and FRAME CURVE |
| 112781 | MOUNTING BOX for FRAME BASIC , FLAT FRAME BASIC, FLAT FRAME CURVE and FRAME CURVE |
| 464107 | LED DRIVER , 3VA, 350mA, with AMP plug, incl. strain relief |

Notes
