




## NEW TRIA 1 SET re-cessed fitting

single-headed LED, 2700K, square, white, 30°, 29W, incl. driver, clip springs

The simplicity and effectiveness of the NEW TRIA 1 SET is captivating. It is available in black, white, or brushed aluminium, in round or square form as well as single-headed or as multi-lamp. Equipped with a powerful, warm white premium COB LED in a tiltable mount, as well as LED driver included in the scope of supply, the set can be used in any lighting situation. The electrical connection is made directly to the 230V mains supply.



## TECHNICAL DATA

|                                     |                        |
|-------------------------------------|------------------------|
| Item no.:                           | 114281                 |
| Lamps included                      | 0                      |
| Primary nominal voltage             | 100-240V ~50/60Hz mA/V |
| Secondary power / secondary voltage | 700 mA/V               |
| Vertical tilting range              | 20 °                   |
| Horizontal rotation range           | 360 °                  |
| Length                              | 18.0 cm                |
| Width                               | 18.0 cm                |
| Height                              | 9.5 cm                 |
| Installation diameter               | 15.0 cm                |
| Installation depth                  | 10.0 cm                |
| Net weight                          | 1.005 kg               |
| Gross weight                        | 1.164 kg               |
| IP Code                             | IP 20                  |
| Safety class                        | I                      |
| Assembly                            | Recessed               |
| Assembly details                    | Ceiling                |
| Dimming technology                  | 1-10V                  |
| Wattage                             | 29 W                   |
| Lumen                               | 2275 lm                |
| Colour temperature                  | 2700 Kelvin            |
| Beam angle                          | 30 °                   |



|                |         |
|----------------|---------|
| Color          | white   |
| CRI            | >80     |
| Binning        | 3       |
| LXXBXX data    | 70/50   |
| Service life   | 30000 h |
| BIG WHITE Page | 433     |

**Notes**

---

---

---

---

---