





## NEW TRIA 68 recessed fitting

LED, 3000K, round, matt black, 38°, 12W, incl. driver, clip springs

The simplicity and effectiveness of the innovative NEW TRIA 68 recessed fitting is captivating. It is available in matt black, matt white or brushed aluminium, in round or square form as well as single-headed or as multi-lamp. Equipped with a powerful, warm white premium COB LED in a tiltable mount, as well as LED driver included in the scope of supply, the set can be used in any lighting situation. The electrical connection is made directly to the 230V mains supply.





## **TECHNICAL DATA**

Item no.:	114380		
Primary nominal voltage	220-240V ~50/60Hz mA/V		
Secondary power / secondary voltage	500 mA/V		
Vertical tilting range	20 °		
Height	4.5 cm		
Diameter	8.2 cm		
Installation diameter	6.8 cm		
Installation depth	5.0 cm		
Net weight	0.271 kg		
Gross weight	0.341 kg		
IP Code	IP 20		
	11		
Safety class	Ш		
Safety class Assembly	Recessed		
Assembly	Recessed		
Assembly details	Recessed Ceiling		
Assembly details  Dimming technology	Recessed  Ceiling  Leading edge,trailing edge		
Assembly Assembly details Dimming technology Wattage	Recessed Ceiling Leading edge,trailing edge 11 W		
Assembly Assembly details Dimming technology Wattage Lumen	Recessed  Ceiling  Leading edge,trailing edge  11 W  890 Im		
Assembly Assembly details Dimming technology Wattage Lumen Colour temperature	Recessed Ceiling Leading edge,trailing edge 11 W 890 Im 3000 Kelvin		
Assembly Assembly details Dimming technology Wattage Lumen Colour temperature Beam angle	Recessed Ceiling Leading edge,trailing edge 11 W 890 Im 3000 Kelvin 38 °		
Assembly  Assembly details  Dimming technology  Wattage  Lumen  Colour temperature  Beam angle  Color	Recessed  Ceiling  Leading edge,trailing edge  11 W  890 Im  3000 Kelvin  38 °  black		





LXXBXX data	70/50
Service life	40000 h
BIG WHITE Page	428

Notes			