





NEW TRIA 68 recessed fitting

LED, 3000K, round, matt white, 38°, 12W, incl. driver, clip springs $\,$

The simplicity and effectiveness of the innovative NEW TRIA 68 recessed fitting is captivating. It is available in matt black, matt white or brushed aluminium, in round or square form as well as single-headed or as multi-lamp. Equipped with a powerful, warm white premium COB LED in a tiltable mount, as well as LED driver included in the scope of supply, the set can be used in any lighting situation. The electrical connection is made directly to the 230V mains supply.





TECHNICAL DATA

Item no.:	114381		
Primary nominal voltage	220-240V ~50/60Hz mA/V		
Secondary power / secondary voltage	500 mA/V		
Vertical tilting range	20 °		
Height	4.5 cm		
Diameter	8.2 cm		
Installation diameter	6.8 cm		
Installation depth	5.0 cm		
Net weight	0.276 kg		
Gross weight	0.345 kg		
IP Code	IP 20		
	II		
Safety class	II .		
Safety class Assembly	II Recessed		
	"		
Assembly	Recessed		
Assembly details	Recessed Ceiling		
Assembly details Dimming technology	Recessed Ceiling Leading edge,trailing edge		
Assembly Assembly details Dimming technology Wattage	Recessed Ceiling Leading edge,trailing edge 11 W		
Assembly Assembly details Dimming technology Wattage Lumen	Recessed Ceiling Leading edge,trailing edge 11 W 890 Im		
Assembly Assembly details Dimming technology Wattage Lumen Colour temperature	Recessed Ceiling Leading edge,trailing edge 11 W 890 Im 3000 Kelvin		
Assembly Assembly details Dimming technology Wattage Lumen Colour temperature Beam angle	Recessed Ceiling Leading edge,trailing edge 11 W 890 Im 3000 Kelvin 38 °		
Assembly Assembly details Dimming technology Wattage Lumen Colour temperature Beam angle Color	Recessed Ceiling Leading edge,trailing edge 11 W 890 Im 3000 Kelvin 38 ° white		





LXXBXX data	70/50
Service life	40000 h
BIG WHITE Page	428

Notes			