





NEW TRIA 68

recessed fitting, LED, 3000K, round, brushed aluminium, 38°, 12W, incl. driver, clip springs

The simplicity and effectiveness of the innovative NEW TRIA 68 recessed fitting is captivating. It is available in matt black, matt white or brushed aluminium, in round or square form as well as single-headed or as multi-lamp. Equipped with a powerful, warm white premium COB LED in a tiltable mount, as well as LED driver included in the scope of supply, the set can be used in any lighting situation. The electrical connection is made directly to the 230V mains supply.





TECHNICAL DATA

| Item no.: | 114386 | | |
|--|---|--|--|
| Primary nominal voltage | 220-240V ~50/60Hz mA/V | | |
| Secondary power / secondary voltage | 500 mA/V | | |
| Vertical tilting range | 20 ° | | |
| Height | 4.5 cm | | |
| Diameter | 8.2 cm | | |
| Installation diameter | 6.8 cm | | |
| Installation depth | 5.0 cm | | |
| Net weight | 0.275 kg | | |
| Gross weight | 0.337 kg | | |
| IP Code | IP 20 | | |
| | II | | |
| Safety class | ll ll | | |
| Safety class Assembly | Recessed | | |
| | <u> </u> | | |
| Assembly | Recessed | | |
| Assembly details | Recessed Ceiling | | |
| Assembly details Dimming technology | Recessed Ceiling Leading edge,trailing edge | | |
| Assembly Assembly details Dimming technology Wattage | Recessed Ceiling Leading edge,trailing edge 11 W | | |
| Assembly Assembly details Dimming technology Wattage Lumen | Recessed Ceiling Leading edge,trailing edge 11 W 890 Im | | |
| Assembly Assembly details Dimming technology Wattage Lumen Colour temperature | Recessed Ceiling Leading edge,trailing edge 11 W 890 Im 3000 Kelvin | | |
| Assembly Assembly details Dimming technology Wattage Lumen Colour temperature Beam angle | Recessed Ceiling Leading edge,trailing edge 11 W 890 Im 3000 Kelvin 38 ° | | |
| Assembly Assembly details Dimming technology Wattage Lumen Colour temperature Beam angle Color | Recessed Ceiling Leading edge,trailing edge 11 W 890 Im 3000 Kelvin 38 ° aluminium | | |





| LXXBXX data | 70/50 |
|----------------|---------|
| Service life | 40000 h |
| BIG WHITE Page | 428 |

| Notes | | | |
|-------|--|--|--|
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |