





H-LIGHT 1

recessed fitting, LED, 2700K, round, black, 20°, 11,5W, incl. driver, clip spring

The H-LIGHT 1 recessed fitting series impresses with its simple and elegant design, the integrated warm-white LED module with its narrow 20° beam angle ensures a discreet and ambience-oriented radiance. Thanks to the LED driver included in the set, the luminaire is immediately ready for connection to a 230V power supply.



TECHNICAL DATA

| | |
|-------------------------------------|----------------------------|
| Item no.: | 114480 |
| Primary nominal voltage | 220-240V ~50/60Hz mA/V |
| Secondary power / secondary voltage | 500 mA/V |
| Vertical tilting range | 15 ° |
| Height | 8.0 cm |
| Diameter | 9.0 cm |
| Installation diameter | 8.0 cm |
| Installation depth | 8.0 cm |
| Net weight | 0.337 kg |
| Gross weight | 0.416 kg |
| IP Code | IP 20 |
| Safety class | II |
| Assembly | Recessed |
| Assembly details | Ceiling |
| Dimming technology | Leading edge,trailing edge |
| Wattage | 11 W |
| Lumen | 265 lm |
| Colour temperature | 2700 Kelvin |
| Beam angle | 20 ° |
| Color | black |
| CRI | >80 |
| Binning | 3 |



| | |
|-----------------------|---------|
| LXXBXX data | 70/50 |
| Service life | 40000 h |
| BIG WHITE Page | 400 |

Notes
