





## H-LIGHT 1

**recessed fitting, LED, 2700K, round, white, 20°, 11,5W, incl. driver, clip spring**

The H-LIGHT 1 recessed fitting series impresses with its simple and elegant design, the integrated warm-white LED module with its narrow 20° beam angle ensures a discreet and ambience-oriented radiance. Thanks to the LED driver included in the set, the luminaire is immediately ready for connection to a 230V power supply.



## TECHNICAL DATA

Item no.:	114481
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary voltage	500 mA/V
Vertical tilting range	15 °
Height	8.0 cm
Diameter	9.0 cm
Installation diameter	8.0 cm
Installation depth	8.0 cm
Net weight	0.343 kg
Gross weight	0.423 kg
IP Code	IP 20
Safety class	II
Assembly	Recessed
Assembly details	Ceiling
Dimming technology	Leading edge, trailing edge
Wattage	11 W
Lumen	265 lm
Colour temperature	2700 Kelvin
Beam angle	20 °
Color	white
CRI	>80
Binning	3

<b>LXXBXX data</b>	70/50
<b>Service life</b>	40000 h
<b>BIG WHITE Page</b>	400

## Notes

---

---

---

---