


## KADUX 2 recessed fitting

double-headed, QPAR111, rectangular, matt white, max. 150W

The KADUX recessed fitting series has a robust housing with appealing, high-quality looks. The lamp holders of this ES111 high-voltage version are multi-directional, allowing individual focus of the light beam. The KADUX 2 recessed fitting comes ready for direct connection to 230V mains.



## **TECHNICAL DATA**

| Item no.:               | 115551          |
|-------------------------|-----------------|
| Socket                  | GU10            |
| Lamp                    | QPAR111         |
| Number of sockets       | 2               |
| Lamps included          | 0               |
| Primary nominal voltage | 230V ~50Hz mA/V |
| Length                  | 37.0 cm         |
| Width                   | 19.5 cm         |
| Height                  | 14.0 cm         |
| Installation length     | 34.5 cm         |
| Installation width      | 17.0 cm         |
| Installation depth      | 15.0 cm         |
| Net weight              | 2.009 kg        |
| Gross weight            | 2.512 kg        |
| IP Code                 | IP 20           |
| Safety class            | I               |
| Assembly                | Recessed        |
| Assembly details        | Ceiling         |
| Wattage                 | 75 W            |
| Color                   | white           |
| BIG WHITE Page          | 435             |
|                         | •               |



## Recommended lamp

| 1001242 | LED lamp , GU10 111mm 30° 2700K                           |
|---------|---|
| 1001570 | LED lamp , QPAR111, GU10, 7W, 3000K 25° silver            |
| 1003094 | LED lamp , QPAR111, GU10, 2700K, 40°, dimmable            |
| 551882  | LED ES111 , lamp, 6.5W, COB LED, 38°, 2700K, not dimmable |

| Notes |  |  |  |
|-------|--|--|--|
|       |  |  |  |
|       |  |  |  |
|       |  |  |  |
|       |  |  |  |
|       |  |  |  |
|       |  |  |  |
|       |  |  |  |
|       |  |  |  |