




KADUX 2 recessed fitting

double-headed, QPAR111, rectangular, brushed aluminium, max. 150W

The KADUX recessed fitting series has a robust housing with appealing, high-quality looks. The lamp holders of this ES111 high-voltage version are multi-directional, allowing individual focus of the light beam. The KADUX 2 recessed fitting comes ready for direct connection to 230V mains.



TECHNICAL DATA

| | |
|-------------------------|-----------------|
| Item no.: | 115556 |
| Socket | GU10 |
| Lamp | QPAR111 |
| Number of sockets | 2 |
| Lamps included | 0 |
| Primary nominal voltage | 230V ~50Hz mA/V |
| Length | 37.0 cm |
| Width | 19.5 cm |
| Height | 14.0 cm |
| Installation length | 34.5 cm |
| Installation width | 17.0 cm |
| Installation depth | 15.0 cm |
| Net weight | 1.955 kg |
| Gross weight | 2.494 kg |
| IP Code | IP 20 |
| Safety class | I |
| Assembly | Recessed |
| Assembly details | Ceiling |
| Wattage | 75 W |
| Color | aluminium |
| BIG WHITE Page | 435 |

Recommended lamp

| | |
|---------|--|
| 1001242 | LED lamp , GU10 111mm 30° 2700K |
| 1001570 | LED lamp , QPAR111, GU10, 7W, 3000K 25° silver |
| 1003094 | LED lamp , QPAR111, GU10, 2700K, 40° , dimmable |
| 551882 | LED ES111 , lamp, 6.5W, COB LED, 38° , 2700K, not dimmable |

Notes
