





KADUX 1 SET recessed fitting

single-headed LED, 3000K, square, matt white, 38°, 9W, incl. driver

The KADUX recessed fitting series has a robust housing with appealing, high-quality looks. This LED set is multi-directional, allowing individual focus of the light beam. The KADUX 1 SET comes ready for direct connection to 230V mains and is available in matt black, matt white or brushed aluminium, as well as in single, double, or triple-headed variations.



TECHNICAL DATA

Item no.:	115701
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary voltage	350 mA/V
Vertical tilting range	25 °
Length	9.0 cm
Width	9.0 cm
Height	8.5 cm
Installation length	8.0 cm
Installation width	8.0 cm
Installation depth	8.0 cm
Net weight	0.385 kg
Gross weight	0.447 kg
IP Code	IP 20
Safety class	II
Assembly	Recessed
Assembly details	Ceiling
Dimming technology	Leading edge, trailing edge
Wattage	7.5 W
Lumen	650 lm
Colour temperature	3000 Kelvin
Beam angle	38 °
Color	white



CRI	>80
Binning	3
LXXBXX data	70/50
Service life	40000 h
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
BIG WHITE Page	436

Notes
