





## KADUX 2 SET recessed fitting

double-headed LED, 3000K, rectangular, matt white, 38°, 15W, incl. driver

The KADUX recessed fitting series has a robust housing with appealing, high-quality looks. This LED set is multi-directional, allowing individual focus of the light beam. The KADUX 2 SET comes ready for direct connection to 230V mains and is available in matt black, matt white or brushed aluminium, as well as in single, double, or triple-headed variations.



## TECHNICAL DATA

|                                     |                        |
|-------------------------------------|------------------------|
| Item no.:                           | 115711                 |
| Lamps included                      | 0                      |
| Primary nominal voltage             | 220-240V ~50/60Hz mA/V |
| Secondary power / secondary voltage | 350 mA/V               |
| Vertical tilting range              | 25 °                   |
| Length                              | 15.0 cm                |
| Width                               | 9.0 cm                 |
| Height                              | 8.5 cm                 |
| Installation length                 | 14.0 cm                |
| Installation width                  | 8.0 cm                 |
| Installation depth                  | 8.0 cm                 |
| Net weight                          | 0.585 kg               |
| Gross weight                        | 0.652 kg               |
| IP Code                             | IP 20                  |
| Safety class                        | II                     |
| Assembly                            | Recessed               |
| Assembly details                    | Ceiling                |
| Dimming technology                  | Leading edge           |
| Wattage                             | 14 W                   |
| Lumen                               | 1290 lm                |
| Colour temperature                  | 3000 Kelvin            |
| Beam angle                          | 38 °                   |

|                |         |
|----------------|---------|
| Color          | white   |
| CRI            | >80     |
| Binning        | 3       |
| LXXBXX data    | 70/50   |
| Service life   | 40000 h |
| BIG WHITE Page | 436     |

## Notes

---

---

---

---