




KADUX 2 SET recessed fitting

double-headed LED, 3000K, rectangular, brushed aluminium, 38°, 15W, incl. driver

The KADUX recessed fitting series has a robust housing with appealing, high-quality looks. This LED set is multi-directional, allowing individual focus of the light beam. The KADUX 2 SET comes ready for direct connection to 230V mains and is available in matt black, matt white or brushed aluminium, as well as in single, double, or triple-headed variations.



TECHNICAL DATA

Item no.:	115716
Lamps included	0
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary voltage	350 mA/V
Vertical tilting range	25 °
Length	15.0 cm
Width	9.0 cm
Height	8.5 cm
Installation length	14.0 cm
Installation width	8.0 cm
Installation depth	8.0 cm
Net weight	0.575 kg
Gross weight	0.642 kg
IP Code	IP 20
Safety class	II
Assembly	Recessed
Assembly details	Ceiling
Dimming technology	Leading edge
Wattage	14 W
Lumen	1290 lm
Colour temperature	3000 Kelvin
Beam angle	38 °

Color	aluminium
CRI	>80
Binning	3
LXXBXX data	70/50
Service life	40000 h
BIG WHITE Page	436

Notes
