



SUPROS

recessed fitting, LED, 3000K, round, white, 4000lm, 60° reflector, 33.5W

The SUPROS light series impresses with its multitude of possible applications, excellent LED technology and its harmonious design. With its very high luminous flux, the SUPROS product family is ideally suited to replace power-hungry, conventional lighting installations. The wide-area reflector included in the delivers can be replaced by reflectors with narrower beam angles which are optionally available. This can be done without the need for tools. With the factory-installed LED driver, all the luminaires in the series are suitable for direct connection to the 230V mains supply.





TECHNICAL DATA

Item no.:	118111	
Lamps included	0	
Primary nominal voltage	al voltage 220-240V ~50/60Hz mA/V	
Secondary power / secondary voltage	950 mA/V	
Vertical tilting range	30 °	
Height	11.0 cm	
Diameter	16.5 cm	
Installation diameter	15.3 cm	
Installation depth	10.7 cm	
Net weight	0.948 kg	
Gross weight	1.099 kg	
IP Code	IP 20	
Safety class	II	
Assembly	Recessed	
Assembly details	Ceiling	
Wattage	36 W	
Lumen	3100 lm	
Colour temperature	3000 Kelvin	
Beam angle	60 °	
Color	white	
CRI	>80	
Binning	3	



		LXXBXX data	70/50
Accessories		Service life	50000 h
114102	REFLECTOR , for SUPROS, 20°, incl. glass and fixing ring	-	
114104	REFLECTOR , for SUPROS, 40°, incl. glass and fixing ring	-	

Notes

Last updated 2021-01-22 13:26:41 | Subject to technical changes