




## **HELIA EL**

LED Indoor recessed ceiling light, white, 3000K,  $35^{\circ}$ 

Rotating and swivelling HELIA LED spot for recessed ceiling installation. The luminaire impresses with its slim design and is therefore ideal for modern lighting concepts. The luminaire is made from aluminium and equipped with a Premium LED module. An additional LED driver is required for operation.



## **TECHNICAL DATA**

Item no.:	156531		
Secondary power / secondary voltage	500 mA/V		
Vertical tilting range	90 °		
Horizontal rotation range	340 °		
Length	11.0 cm		
Width	11.5 cm		
Height	10.5 cm		
Installation diameter	6.8 cm		
Installation depth	5.0 cm		
Net weight	0.295 kg		
Gross weight	0.419 kg		
	IP 20		
IP Code	IP 20		
IP Code Safety class	IP 20		
	"		
Safety class	III		
Safety class Assembly	III Recessed		
Safety class Assembly Assembly details	III Recessed Ceiling,Wall		
Safety class Assembly Assembly details Wattage	III  Recessed  Ceiling, Wall  9 W		
Safety class Assembly Assembly details Wattage Lumen	III  Recessed  Ceiling, Wall  9 W  800 Im		
Safety class  Assembly  Assembly details  Wattage  Lumen  Colour temperature	III Recessed Ceiling,Wall 9 W 800 Im 3000 Kelvin		
Safety class  Assembly  Assembly details  Wattage  Lumen  Colour temperature  Beam angle	III  Recessed  Ceiling, Wall  9 W  800 Im  3000 Kelvin		
Safety class Assembly Assembly details Wattage Lumen Colour temperature Beam angle Color	III  Recessed  Ceiling, Wall  9 W  800 Im  3000 Kelvin  35 °  white		



## Accessories

464091	LED DRIVER , 9VA, 500mA, incl. strain relief
--------	--

LXXBXX data	70/50
Service life	30000 h
Minimum ambient temperature	-20 °C
Maximum ambient temperature	50 °C
BIG WHITE Page	391

Notes			