



## LED PANEL 360

recessed fitting, 4000K, round, white, without a driver, 40W

The LED PANEL 360 comes in a number of different light colours and offers a modern and space-saving solution for efficient base lighting. Due to the variable constant current power supply of 1000mA to 1050mA, various standard or dimmable drivers can be used. With this product you reach a pleasant, homogeneous and glare-free lighting feeling.

### TECHNICAL DATA

Item no.:	158664
Lamps included	0
Secondary power / secondary voltage	10001050 mA/V
Height	4.0 cm
Diameter	60.0 cm
Installation diameter	59.0 cm
Installation depth	6.0 cm
Net weight	2.507 kg
Gross weight	3.297 kg
IP Code	IP 20
Safety class	III
Assembly	Recessed
Assembly details	Ceiling
Wattage	34 W
Lumen	2930 lm
Colour temperature	4000 Kelvin
Beam angle	120 °
Color	white
CRI	>80
UGR ≤	22
Binning	6
LXXBXX data	70/50

Service life	30000 h
--------------	---------

## Accessories

464032	TCI LED DRIVER , 50VA, 350-1050mA, dip switch, incl. strain relief, DALI dimmable
464170	LED DRIVER , 40W, 1000mA, incl. strain relief
464176	LED DRIVER , 40W, 1000mA, incl. strain relief, dimmable
464804	LED DRIVER , 40W, 1050mA, triac dimmable

## Notes

---

---

---

---

---