



D-RECTION

spot for 240V 3-phase track, HIT, black / chrome, max. 70W, incl. 3-phase adapter

Adjustable high-voltage spot D-RECTION with suitable adapter for the 240V 3-phase track system. To customize this professional spot with incorporated G12 socket to any location, reflectors with various beam angles are available separately. The electronic ballast required to operate the discharge lamp as well as a deco ring are included in the scope of supply.

TECHNICAL DATA

Item no.:	153730
Socket	G12
Lamp	HIT-CE
Number of sockets	1
Lamps included	0
Primary nominal voltage	230V ~50Hz mA/V
Tilt range	180 °
Horizontal rotation range	350 °
Length	26.0 cm
Width	9.5 cm
Height	22.0 cm
Net weight	0.818 kg
Gross weight	0.957 kg
IP Code	IP 20
Safety class	I
Assembly	Surface
Assembly details	Ceiling, Track Ceiling
Wattage	81 W
Color	black

Accessories

153741	REFLECTOR , 12° for D-RECTION and D-RECTION ELITE
153742	REFLECTOR , 24° for D-RECTION and D-RECTION ELITE
153743	REFLECTOR , 38° for D-RECTION 70W and D-RECTION ELITE
153746	REFLECTOR , 60° for D-RECTION and D-RECTION ELITE

Notes
