




## TEC KALU double

black, 24°, 3000K, incl. 3-circuit adapter

The futuristic 240V TEC KALU with an appropriate adapter for the 3-circuit 240V track system has individually rotating and swivelling lamp heads with warm-white and dimmable premium LEDs. The built-in LED driver is located within the main structure. TEC KALU is supplied ready for direct connection to the 230V mains voltage supply.



## TECHNICAL DATA

Item no.:	1001427
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary voltage	700 mA/V
Vertical tilting range	120 °
Horizontal rotation range	360 °
Length	29.5 cm
Width	17.0 cm
Height	15.5 cm
Net weight	1.67 kg
Gross weight	2.133 kg
IP Code	IP 20
Safety class	I
Assembly	Surface
Assembly details	Track Ceiling
Dimming technology	trailing edge
Wattage	31 W
Lumen	1900 lm
Colour temperature	3000 Kelvin
Beam angle	24 °
Color	black
CRI	>80
Binning	6



<b>LXXBXX data</b>	70/50
<b>Service life</b>	40000 h
<b>Minimum ambient temperature</b>	-20 °C
<b>Maximum ambient temperature</b>	40 °C
<b>BIG WHITE Page</b>	486

**Notes**

---

---

---

---

---