


EURO SPOT TRACK black

3000K, 12°, incl. 3-circuit adapter

Rotating and swivelling EURO SPOT TRACK 240V LED spotlight, with a compact design with suitable adapter for the 3-circuit 240V track system. The LED light source is installed in the cylindrical lamp head in the factory. The spotlight, which is available with several housing colours and beam angles, has a high light output thanks to its simple and timeless appearance.



TECHNICAL DATA

| Item no.: | 1001476 | | |
|-------------------------------------|------------------------|--|--|
| Primary nominal voltage | 220-240V ~50/60Hz mA/V | | |
| Secondary power / secondary voltage | 1500 mA/V | | |
| Vertical tilting range | 90 ° | | |
| Horizontal rotation range | 350 ° | | |
| Length | 25.5 cm | | |
| Height | 29.5 cm | | |
| Diameter | 14.5 cm | | |
| Net weight | 3.097 kg | | |
| Gross weight | 3.515 kg | | |
| IP Code | IP 20 | | |
| Safety class | I | | |
| Assembly | Surface | | |
| Assembly details | Track Ceiling | | |
| Wattage | 61 W | | |
| Lumen | 5500 lm | | |
| Colour temperature | 3000 Kelvin | | |
| Beam angle | 12 ° | | |
| Color | black | | |
| CRI | >80 | | |
| Binning | 3 | | |
| LXXBXX data | 70/50 | | |
| | • | | |





| Service life | 50000 h |
|----------------|---------|
| BIG WHITE Page | 495 |

| Notes | | | |
|-------|--|--|--|
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |