




## 3~ EURO SPOT TRACK

black 3000K 36° incl. 3-circuit adapter

The EURO SPOT swivelling and tilting LED spotlight in a compact design is suitable for the high-voltage 3-circuit track system with the matching adapter. A COB LED module is factory-fitted inside the cylindrical light head. This spotlight, available in different colours, stands out with its simple and timeless look.



## TECHNICAL DATA

|                                     |                           |
|-------------------------------------|---------------------------|
| Item no.:                           | 1002681                   |
| Primary nominal voltage             | 220-240V ~50/60Hz mA/V    |
| Secondary power / secondary voltage | 500 mA/V                  |
| Vertical tilting range              | 90 °                      |
| Horizontal rotation range           | 350 °                     |
| Length                              | 17.3 cm                   |
| Height                              | 22.1 cm                   |
| Diameter                            | 12.5 cm                   |
| Net weight                          | 1.396 kg                  |
| Gross weight                        | 1.825 kg                  |
| IP Code                             | IP 20                     |
| Safety class                        | I                         |
| Assembly                            | Surface                   |
| Assembly details                    | Track Ceiling, Track Wall |
| Wattage                             | 20 W                      |
| Lumen                               | 1800 lm                   |
| Colour temperature                  | 3000 Kelvin               |
| Beam angle                          | 36 °                      |
| Color                               | black                     |
| CRI                                 | >80                       |
| Binning                             | 3                         |
| LXXBXX data                         | 70/50                     |



|                                    |         |
|------------------------------------|---------|
| <b>Service life</b>                | 40000 h |
| <b>Maximum ambient temperature</b> | 30 °C   |
| <b>BIG WHITE Page</b>              | 495     |

**Notes**

---

---

---

---

---