а. л л. ы ы 111 ы . л 1 л






3~ SUPROS TRACK

LED 3-circuit system luminaire white 3000K CRI90 60° 3380Im reflector incl. 3-circuit adapter

The SUPROS light series impresses with its multitude of possible applications, excellent LED technology and its harmonious design. With its very high luminous flux, the SUPROS product family is ideally suited to replace power-hungry, conventional lighting installations. The wide-area reflector included in the delivers can be replaced by reflectors with narrower beam angles which are optionally available. This can be done without the need for tools. With the factory-installed LED driver, all the luminaires in the series are suitable for direct connection to the 230V mains supply.



TECHNICAL DATA

Item no.:	1003296			
Lamps included	0			
Primary nominal voltage	220-240V ~50/60Hz mA/V			
Secondary power / secondary voltage	950 mA/V			
Vertical tilting range	190 °			
Horizontal rotation range	350 °			
Length	24.5 cm			
Height	21.5 cm			
Diameter	12.7 cm			
Net weight	1.61 kg			
Gross weight	1.804 kg			
IP Code	IP 20			
Safety class	1			
Assembly	Surface			
Assembly details	sembly details Track Ceiling			
Wattage	36 W			
Lumen	3380 lm			
Colour temperature	3000 Kelvin			
Beam angle	60 °			
Color	white			
CRI	>90			
Binning	3			



		LXXBXX data	70/50
Accessories		Service life	50000 h
		Ambient temperature	25 °C
114102	REFLECTOR , for SUPROS, 20°, incl. glass and fixing ring	BIG WHITE Page	489
114104	REFLECTOR , for SUPROS, 40°, incl. glass and fixing ring	_	

Notes