




### 3~ SUPROS TRACK

**LED 3-circuit system luminaire black 4000K CRI90 60°  
3520lm reflector incl. 3-circuit adapter**

The SUPROS light series impresses with its multitude of possible applications, excellent LED technology and its harmonious design. With its very high luminous flux, the SUPROS product family is ideally suited to replace power-hungry, conventional lighting installations. The wide-area reflector included in the delivers can be replaced by reflectors with narrower beam angles which are optionally available. This can be done without the need for tools. With the factory-installed LED driver, all the luminaires in the series are suitable for direct connection to the 230V mains supply.



### TECHNICAL DATA

|                                     |                        |
|-------------------------------------|------------------------|
| Item no.:                           | 1003297                |
| Lamps included                      | 0                      |
| Primary nominal voltage             | 220-240V ~50/60Hz mA/V |
| Secondary power / secondary voltage | 950 mA/V               |
| Vertical tilting range              | 190 °                  |
| Horizontal rotation range           | 350 °                  |
| Length                              | 24.5 cm                |
| Height                              | 21.5 cm                |
| Diameter                            | 12.7 cm                |
| Net weight                          | 1.606 kg               |
| Gross weight                        | 1.827 kg               |
| IP Code                             | IP 20                  |
| Safety class                        | I                      |
| Assembly                            | Surface                |
| Assembly details                    | Track Ceiling          |
| Wattage                             | 36 W                   |
| Lumen                               | 3520 lm                |
| Colour temperature                  | 4000 Kelvin            |
| Beam angle                          | 60 °                   |
| Color                               | black                  |
| CRI                                 | >90                    |
| Binning                             | 3                      |

## Accessories

|        |  |
|--------|--|
| 114102 | REFLECTOR , for SUPROS, 20°, incl. glass and fixing ring |
| 114104 | REFLECTOR , for SUPROS, 40°, incl. glass and fixing ring |

|                     |         |
|---------------------|---------|
| LXXBXX data         | 70/50   |
| Service life        | 50000 h |
| Ambient temperature | 25 °C   |
| BIG WHITE Page      | 489     |

## Notes

---

---

---

---

---