



## 3~ NUMINOS® PHASE M

### 3 phase system light black/black 4000K 60°

No two projects are the same. But many projects demand a coherent lighting and design concept. NUMINOS® is a perfectly coordinated lighting system that harmonises function, design and technology. For planners and doers, for every requirement and for maximum variety with minimum effort. From hotels and offices to commercial or private rooms. From application to technology to design in detail: the modular downlights and spotlights can be configured exactly as required by the design or spatial conditions in question. The more multifaceted your project is, the more you can benefit from the intelligent NUMINOS® lighting family. Thanks to the wide selection of modules, there is a suitable solution for every need. The NUMINOS® lighting system, which can be configured and combined, offers over a thousand possibilities. Like this pendant light, which, with its light cone directed downwards, can be used to create accent lighting above furnishings such as tables and counters in living spaces, shops or restaurants. With the best workmanship and light quality, which is infinitely variable thanks to the integrated LED driver (phase dimming). This means that easy installation is a mere formality. When will you choose SLV's modular variety? Here you can find the configurator: [www.NUMINOS.SLV.com](http://www.NUMINOS.SLV.com)

## TECHNICAL DATA

Item no.:	1004180
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary voltage	500 mA/V
Vertical tilting range	90 °
Horizontal rotation range	350 °
Length	18.5 cm
Height	16.5 cm
Diameter	8.5 cm
Net weight	0.787 kg
Gross weight	1.094 kg
Safety class	I
Assembly details	Track Ceiling
Dimming technology	trailing edge
Wattage	20.1 W
Lumen	1880 lm
Colour temperature	3000 Kelvin
Beam angle	60 °
Color	black
CRI	>90
UGR ≤	22
Binning	3
LXXBXX data	70/50



Service life	50000 h
BIG WHITE Page	45

**Notes**

---

---

---

---

---