


1-CIRCUIT SUR-FACE-MOUNTED TRACK

240V track, silver-grey, 2 m

Aluminium carrier track of the 1-phase high-voltage surface-mounted track system. Installation can be done through the existing holes in the profile directly onto the wall or the ceiling. The surface-mounted version of this system is available in several colour versions. Alternatively, there is a recessed version available too.



TECHNICAL DATA

| Item no.: | 143022 |
|------------------|---------------------|
| Nominal voltage | 220-240V ~50/60Hz V |
| Length | 200.0 cm |
| Width | 3.5 cm |
| Height | 1.8 cm |
| Net weight | 1.025 kg |
| Gross weight | 1.26 kg |
| IP Code | IP 20 |
| Safety class | I |
| Assembly | Surface |
| Assembly details | Ceiling,Wall |
| Color | grey |
| BIG WHITE Page | 528 |
| | |

| | | | | | | | 4 | | | | 4 | | | 4 | | 4 | | - | ч | - | 4 | ч, | 4 | ч, | 4 | 4 | 4 | | | | | | | | | |
|---|-----|----|---|----|----|---|---|---|---|---|---|---|---|---|----|----|---|----|---|---|---|----|----|----|---|----|---|---|---|----|---|----|-----|-----|----|---|
| | - 4 | | | a, | a, | J | J | J | J | a | J | J | J | J | ä | a, | ä | ā, | ä | | | | | | | | | | | | | | | | | |
| ı | 1 1 | LL | 1 | J | J | J | J | J | ä | 4 | ā | J | J | J | J | J | 4 | | 4 | | | 1 | | ı | | 1 | 4 | 1 | 1 | J, | 1 | ١, | , د | . د | ١. | ı |
| | | | | | п | | | п | | м | | п | 4 | 4 | Э. | 1 | п | | 1 | | п | 1 | т. | | | т. | п | 4 | | | | | | | | |



Accessories

| 1002845 | Steel wire suspension for EUTRAC® , S-TRACK and 1 phase tracks, 5m, set of two |
|---------|--|
| 1004784 | 1~ track cover , grey 2m |

| Notes | | | | |
|-------|--|--|--|--|
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |