




BIMA 1

spot for 240V 1-phase track, single-headed, QPAR51, matt white, max. 50W, incl. 1-phase adapter

Adjustable high-voltage spot BIMA 1 with suitable adapter for the 240V 1-phase track system. The luminaire is made of aluminium and, thanks to the GU10 socket, is suitable for both halogen and LED lamps.



TECHNICAL DATA

| | |
|---------------------------|------------------------|
| Item no.: | 143441 |
| Socket | GU10 |
| Lamp | QPAR51 |
| Number of sockets | 1 |
| Lamps included | 0 |
| Primary nominal voltage | 220-240V ~50/60Hz mA/V |
| Tilt range | 200 ° |
| Horizontal rotation range | 350 ° |
| Length | 8.0 cm |
| Height | 16.0 cm |
| Diameter | 6.0 cm |
| Net weight | 0.251 kg |
| Gross weight | 0.319 kg |
| IP Code | IP 20 |
| Safety class | II |
| Assembly | Surface |
| Assembly details | Ceiling, Track Ceiling |
| Wattage | 50 W |
| Color | white |
| BIG WHITE Page | 515 |

Recommended lamp

| | |
|---------|---|
| 1001030 | LED QPAR51 GU10 , lamp, 38°, 2700K, 400 lm, dimmable |
| 1005080 | LED lightbulb QPAR51 , GU10, 3000K, black |

Notes
