





## HELIA 50

spot for 1-circuit high-voltage track, LED, 3000K, white, 35°, incl. 1-circuit adapter

Adjustable LED spot HELIA 60 with suitable adapter for the 240V 1-circuit track system. The luminaire impresses with its slim design and is therefore ideal for modern lighting concepts. The luminaire is made from aluminium and equipped with a Premium LED module.



## TECHNICAL DATA

|                                     |                           |
|-------------------------------------|---------------------------|
| Item no.:                           | 143581                    |
| Primary nominal voltage             | 220-240V ~50/60Hz mA/V    |
| Secondary power / secondary voltage | 500 mA/V                  |
| Vertical tilting range              | 90 °                      |
| Horizontal rotation range           | 350 °                     |
| Length                              | 14.0 cm                   |
| Height                              | 12.0 cm                   |
| Diameter                            | 5.5 cm                    |
| Net weight                          | 0.328 kg                  |
| Gross weight                        | 0.456 kg                  |
| IP Code                             | IP 20                     |
| Safety class                        | I                         |
| Assembly                            | Surface                   |
| Assembly details                    | Track Ceiling, Track Wall |
| Wattage                             | 11 W                      |
| Lumen                               | 750 lm                    |
| Colour temperature                  | 3000 Kelvin               |
| Beam angle                          | 35 °                      |
| Color                               | white                     |
| CRI                                 | >90                       |
| Binning                             | 6                         |
| LXXBXX data                         | 70/50                     |



|                                    |         |
|------------------------------------|---------|
| <b>Service life</b>                | 30000 h |
| <b>Minimum ambient temperature</b> | -20 °C  |
| <b>Maximum ambient temperature</b> | 50 °C   |
| <b>BIG WHITE Page</b>              | 521     |

**Notes**

---

---

---

---

---