




SUPROS

spot for 240V 3-phase track, LED, 4000K, white, 60° reflector, 28W, incl. 3-phase adapter

The SUPROS light series impresses with its multitude of possible applications, excellent LED technology and its harmonious design. With its very high luminous flux, the SUPROS product family is ideally suited to replace power-hungry, conventional lighting installations. The wide-area reflector included in the delivers can be replaced by reflectors with narrower beam angles which are optionally available. This can be done without the need for tools. With the factory-installed LED driver, all the luminaires in the series are suitable for direct connection to the 230V mains supply.



TECHNICAL DATA

Item no.:	152681
Lamps included	0
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary voltage	750 mA/V
Vertical tilting range	190 °
Horizontal rotation range	350 °
Length	24.5 cm
Height	21.5 cm
Diameter	12.7 cm
Net weight	1.566 kg
Gross weight	1.748 kg
IP Code	IP 20
Safety class	I
Assembly	Surface
Assembly details	Ceiling, Track Ceiling
Wattage	31 W
Lumen	2850 lm
Colour temperature	4000 Kelvin
Beam angle	60 °
Color	white
CRI	>80
Binning	3

LXXBXX data	70/50
Service life	50000 h

Accessories

1000679	ANTI-GLARE CAPS , for SUPROS, black
1000680	ANTI-GLARE CAPS , for SUPROS, white
114102	REFLECTOR , for SUPROS, 20°, incl. glass and fixing ring
114104	REFLECTOR , for SUPROS, 40°, incl. glass and fixing ring

Notes
