




KALU TRACK

spot for 240V 3-phase track, QR111, silver-grey, max. 50W, incl. 3-phase adapter

Adjustable spot KALU TRACK with suitable adapter for the 240V 3-phase track system. Conceived as an extension to the popular KALU series, this track spot takes on the shape of the product family. By means of the combination of track adapter and transformer, the operation of low-voltage light sources on a high-voltage track is ensured. To meet all lighting requirements, we alternatively offer versions with GX53 socket and such with incorporated Philips LED modules for the 1- and 3-phase systems.



TECHNICAL DATA

| | |
|-------------------------------------|------------------------|
| Item no.: | 153584 |
| Socket | G53 |
| Lamp | QR111 |
| Number of sockets | 1 |
| Lamps included | 0 |
| Primary nominal voltage | 230V ~50Hz mA/V |
| Secondary power / secondary voltage | 12 mA/V |
| Tilt range | 90 ° |
| Horizontal rotation range | 350 ° |
| Height | 18.0 cm |
| Diameter | 12.0 cm |
| Net weight | 0.32 kg |
| Gross weight | 0.492 kg |
| IP Code | IP 20 |
| Safety class | II |
| Assembly | Surface |
| Assembly details | Ceiling, Track Ceiling |
| Wattage | 50 W |
| Color | grey |
| BIG WHITE Page | 492 |



Recommended lamp

| | |
|--------|--|
| 560232 | PHILIPS MASTER LED AR111 , CRI90, 15W, 40°, 2700K, dimmable |
| 560234 | PHILIPS MASTER LED AR111 , CRI90, 15W, 40°, 3000K, dimmable |

Notes
