


S-TRACK 3-phase surface-mounted track

240V track, black, 2 m

Aluminium bearing track of the 240V 3-phase surface-mounted track system. Installation can be done through the existing holes in the profile directly onto the wall or the ceiling. The surface-mounted version of this system is available in several colours and lengths. Alternatively, there is a recessed version available too.



TECHNICAL DATA

Item no.:	175020
Nominal voltage	220-250V ~50Hz V
Length	199.5 cm
Width	3.6 cm
Height	3.6 cm
Net weight	1.764 kg
Gross weight	2.19 kg
IP Code	IP 20
Safety class	I
Assembly	Surface
Assembly details	Ceiling, Wall
Color	black

							4				4			4		4		4	4	4	4	ч	4	4	4	4	4									
	- 4	- 4		J	J.	J	J	J	J.	a,	J	J	J	J	J,	a,	a,	a,	J,																	
ı,	L	l l	J	J	1	J	J	J.	4	ä	J	J	a,	J	ä	J	ä		4			J		J.		ı	J	ı	J.	J	J.	١,	١,	1	ı	ı
					4					4		1	1	-1	1	1	а.	1	1	1	1	1	1	1	1	т.	4	1								



Accessories

1002845	Steel wire suspension for EUTRAC® , S-TRACK and 1 phase tracks, 5m, set of two
---------	--

Notes			